

Section 4-4-C-3 CLIMATIC AND GEOGRAPHIC DESIGN CRITERIA.

Table No. R301.2(1) of Section R301.2.1 of the International Residential Code is hereby repealed and a new Table No. R301.2(1) is added to read as follows:

Ground snow load (inches)		20	Winter design temperature ^h	6 ⁰ F
Wind speed (mph) ^d		90	Ice barrier underlayment ^h	Yes
Seismic design category		A	Flood Hazard ^g	6/17/2002
SUBJECT TO DAMAGE FROM	Weathering ^a	Severe	Air Freezing index ⁱ	1000
	Frost depth ^b	36"	Mean annual temperature ^j	54.7 ⁰ F
	Termite ^c	Moderate/Heavy		

a. Weathering may require a higher strength concrete or grade of masonry than necessary to satisfy the structural requirements of this code. The weathering column shall be filled in with the weathering index (i.e., "negligible," "moderate" or "severe") for concrete as determined from the Weathering Probability Map [Figure R301.2(3)]. The grade of masonry units shall be determined from ASTM C 34, C 55, C 62, C 73, C 90, C 129, C 145, C 216 or C 652.

b. The frost line depth may require deeper footings than indicated in Figure R403.1(1). The jurisdiction shall fill in the frost line depth column with the minimum depth of footing below finish grade.

c. The jurisdiction shall fill in this part of the table with "very heavy," "moderate to heavy," "slight to moderate," or "none to slight" in accordance with Figure R301.2(6) depending on whether there has been a history of local damage.

d. The jurisdiction shall fill in this part of the table with the wind speed from the basic wind speed map [Figure R301.2(4)]. Wind exposure category shall be determined on a site-specific basis in accordance with Section R301.2.1.4.

e. The outdoor design dry-bulb temperature shall be selected from the columns of 97 ½-percent values for winter from Appendix D of the 2006 International Plumbing Code.

Deviations from the Appendix D temperatures shall be permitted to reflect local weather experience as determined by the Building Official.

f. The jurisdiction shall fill in this part of the table with the Seismic Design Category determined from Section R301.2.(2).

g. The jurisdiction shall fill in this part of the table with (a) the date of the jurisdiction's entry into the National Flood Insurance Program (date of adoption of the first code or ordinance for management of flood hazard areas), (b) the date(s) of the currently effective FIRM and FBFM, or other flood hazard map adopted by the community, as may be amended.

h. In accordance with Sections R905.2.7.1, R905.4.3.1, R905.5.3.1, R905.6.3.1, R905.7.3.1 and R905.8.3.1, where there has been a history of local damage from the effects of ice damming, the jurisdiction shall fill in this part of the table with "YES." Otherwise, the jurisdiction shall fill in this part of the table with "NO."

i. The jurisdiction shall fill in this part of the table with the 100-year return period air freezing index (BF-days) from Figure R403.3(2) or from the 100-year (99%) value on the National Climatic Data Center data table "Air Freezing Index- USA Method (Base 32° Fahrenheit)" at www.ncdc.noaa.gov/fpsf.html.

j. The jurisdiction shall fill in this part of the table with the mean annual temperature from the National Climatic Data Center data table "Air Freezing Index- USA Method (Base 32° Fahrenheit)" at www.ncdc.noaa.gov/fpsf.html.